

ONE OR TWO AXLES REAR HALF-PIPE TIPPING FARM TRAILER WITH UNDER TIPPER CYLINDER



Please note that data and pictures give an approximate idea without binding the builder

TYPE	TANK DIMENSION	CAPACITY	TARE kg.	Road Full load Type-approved QL.	SINGLE USED TYRES	Oil used while tipping
FC91D	4700x2500x1200	Mt ³ 12	2300	50 o 60*	385/65R22.5	Lt. 16
FC140D	4800x2500x1230	Mt ³ 14	3350	100o120o140	385/65R22.5	Lt. 19
FC160D	5980x2530x1500	Mt ³ 17,5	4000	140	385/65R22.5	Lt. 30

BASIC EQUIPMENT

- Rear half-pipe hydraulic farm tipper, quick- release coupling with under tipper cylinder
- Chassis on a hard single axle for FC91D type
- Chassis on tandem suspensions with two fixed axles for FC140D type
- Chassis on bogie suspensions with two fixed axles for FC160D type
- FE510 smooth sheet-steel half-pipe
- Hydraulic stabilizer
- Mechanical brakes for FC91D type
- Hydraulic or pneumatic brakes for FC140D – FC160D type
- Tailgate sealed with adhesive mousse profile: mechanical for FC91D-FC160D; hydraulic for FC140D
- Light system and documents for registration in Italian and CE certification
- Standard paint: green frame, antirust inside half-pipe, yellow outside
- Top speed allowed: 40 km/h



OPTIONAL ON REQUEST FOR A FEE

*Hydraulic brakes type-approved at 60 quintals full load; steering rear axle; upper sideboards, manual opening to unload cereals; tool box; hand-wash basin; hydraulic rear-gate, central pole for tarpaulin; substitute wheels; new tyres; tipping over by a pump with hydraulic motor and push-bottom panel; mechanical or electric covering system; for FC160D: axles with strengthened brake (400x80), tandem suspensions with 300x90 or 400x80 brake; two colors painting for the external part of the half-pipe