

# THREE AXLES REAR HALF-PIPE FARM TIPPING TRAILER WITH FRONTAL CYLINDER



Please note that data and pictures give an approximate idea without binding the builder

TYPE	TANK DIMENSION	CAPACITY	TARE kg.	Road Full load Type-approved QL.	SINGLE, USED TYRES
FC270D	5960x2530x1689	Mt <sup>3</sup> 22	6600	200	425/65R22.5
FC270D	6600x2540x1850	Mt <sup>3</sup> 26	6900	200	425/65R22.5
FC270D	7850x2550x1910	Mt <sup>3</sup> 30	7350	200	425/65R22.5

## BASIC EQUIPMENT

- Rear half-pipe hydraulic farm tipper with hydraulic motor and push-button panel. Frontal cylinder
- Telaio su tre assi ravvicinati, freno 400x80, 1° e 3° asse sterzanti a bloccaggio idraulico, sospensione su tridem con balestre paraboliche
- Adjustable highF3-Super towbar
- Domex, smooth sheet-steel half-pipe, chassis structure in FE510
- Hydraulic stabilizer
- Hydraulic or pneumatic brakes
- Watertight, mechanical rear-gate, with riveted rubber profile
- Light system and documents for registration in Italian and CE certification
- Standard paint: green frame, antirust inside half-pipe, white outside
- Top speed allowed: 40 km/h



## OPTIONAL ON REQUEST FOR A FEE

Upper sideboards, manual opening to unload cereals, toolbox, hand-wash basin, hydraulic rear-gate, central pole for tarpaulin, substitutive new tyres (385/65R225.5 – 445/65R22.5 – 500/60R22.5 – 560/60R22.5 – 600/50R22.5), mechanical or electric covering system, different painting or two colors painting for the external part of the half-pipe, axles with strengthened brake 406x120. self-controlled steering: such application is recommended for vehicles which require a greater maneuverability in both directions of travel, allowing also a lower consumption of the tires due to the reduction of drag.



Via Olanda 8 – Loc. San Giacomo – 06049 Spoleto (PG) Italia  
Tel. 0743520837 Fax 0743270196  
www.caporiccirimorchi.com caporiccirimorchi@libero.it