

# THREE AXLES PLATFORM



Please note that data and pictures give an approximate idea without binding the builder

Type	Loading area available dimensions	APPROXIMATE TARE Kg	Road Full load Type-approved QL.	TWIN, USED TYRES
FC250C	8650x2550	6000	200	235/75R17.5
FC260CR -1	7600x2550	5200	200	235/75R17.5
FC260CR -2	9000x2550	5800	200	235/75R17.5
FC260CR -3	10000x2550	5950	200	235/75R17.5

## BASIC EQUIPMENT

- Chassis on three close axles, 1<sup>st</sup> and 3<sup>rd</sup> steering axles, tridem suspensions with parabolic leaf springs
- Chequered sheet
- F3 towbar
- Hydraulic stabilizer
- Hydraulic or pneumatic brakes
- **Type FC250C:** hydraulic, rear tilting with two single acting cylinders
- **Type FC260CR:** fixed platform with rear hydraulic loading ramps and rear stands
- Light system and documents for registration in Italian and CE certification
- Standard paint: red
- Top speed allowed: 40 km/h



## OPTIONAL ON REQUEST FOR A FEE

Manual rear little board, hydraulic little board, poles to carry bales, toolbox, hand-wash basin, substitutive or new tyres (single or twin), personalized painting, containers arrangement, iron container.